

SHUKY

轮胎式移动破碎站

Wheel Mounted Mobile Crushing Station



01 产品简介

Brief Introduction



移动式破碎站主要用于冶金、化工、建材、水电等经常需要搬迁作业的物料加工，特别是用于高速公路、铁路、水电工程等流动性石料的破碎筛分作业。用户可根据加工原料的种类，规模和成品物料要求的不同采用多种配置形式。近几年在建筑垃圾资源再利用工程方面做出卓越贡献。

Mobile crushing station is mainly used to process materials in metallurgy, chemical industry, building construction, hydropower project, etc. which needs to be moved around frequently. It is especially applied in the crushing and screening work of movable materials in highway, railway and hydropower engineering project. Users can adopt a variety of configuration forms according to different kinds of raw material processed, scales, and final products. In recent years, it has made outstanding contributions in the construction wastes recycling engineering.

一体化整套机组，降低了分体组件对场地基础设施的要求及辅助设施安装作业的难度，可节省大量基建及迁址费用。能够对物料进行现场破碎，并可随原料开采面的推进而移动，从而大量降低了物料的运输费用。真正为客户提供高效、低成本项目运营的硬件设施。

Integrated mobile station reduces the difficulties in building infrastructure for separated components and installing auxiliary facilities. It can save a lot of infrastructure and relocation cost. Besides, it also can conduct crushing work on site and move according to the sites of raw materials, which greatly reduce the transportation cost. The station truly provides customers with high efficient and low-cost hardware facilities for the operation of project.

02 性能特点

Features

1. 模块化设计，机动灵活，组合多样化。车载牵引，结构紧凑，稳定坚固，使破碎站无论在工作现场还是公路上都能够满足机动性需求，各种机型能够快速与其他机型匹配组合，满足生产作业的不同需求。

1. Modular design makes it flexible and can be combined with other machines freely. Wheel-mounted traction, compact structure and stability make mobile crushing station satisfy the demand of mobility no matter at the work site or on the road. Various models can quickly combine with other models to meet the different needs of production.

2. 现场作业，降低物料运输费用。各机型组合作业，能够对物料进行现场破碎，破碎筛分后成品可直接满足客户要求，极大降低了物料的运输成本。

2. On-site working helps reduce transportation cost. The work is conducted by various equipments which can crush the materials on the site. The finished products can meet the needs of customers directly, which reduces the material transportation cost.

3. 适应性强，按需定制。该破碎站可配备独立发电机组，即使无法采用当地电网，该机依旧可以正常作业；同时客户可根据现场、物料、粒型等不同进行特别定制。

3. Strong adaptability and on-demand customization. This crushing station is equipped with independent generator. The machine can work normally even there is no local power. At the same time, we can customize mobile crushing plant according to customer's site, quality of materials and shape of products.

4. 结构紧凑，性能可靠。移动破碎站集我公司性能优异的给料机、破碎机、振动筛、车载电动机、控制箱于一体，结构紧凑，运行稳定可靠。

4. Compact structure and reliable performance. Mobile crushing station integrates the superior vibrating feeder, crushers, vibrating screen, vehicle motor and control box as a whole, which makes the station have compact structure and reliable running.

5. 承载结构合理，安装快捷。只需对支撑部位简单处理，移动站可立即投入运行。如需转场操作，可方便的进行拆解和运输，无任何剩余损耗。

5. Reasonable bearing structure and fast installation. Mobile crushing station can be put into use just after simple processing of supporting parts. It is convenient to disassemble and transport without any residual loss if it need be moved to other places.





项目 Item	单位 Unit	MG938E69	MG1124E170	MG1349E912	MG1349SK87	MG1349SK110
运输长度 Transportation Length	mm	11900	13100	14600	14600	15400
运输宽度 Transportation Width	mm	2550	2550	1950	1550	1950
运输高度 Transportation Height	mm	3650	4450	4500	4500	4500
最大长度 Maximum Length	mm	12100	13300	14600	14600	15400
最大宽度 Maximum Width	mm	2900	2950	3300	3300	3300
最大高度 Maximum Height	mm	4060	4810	5300	5300	5700
重量 Weight	t	39	57	83	65	92
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装三轴 Tri-axial	并装三轴 Tri-axial	并装三轴 Tri-axial	并装三轴 Tri-axial
破碎机型号 Crusher		PE-600×900	PE-750×1060	PE-900×1200	SKJ870×1100	SKJ1100×1300
最大进料 Max Feeding Size	mm	480	630	750	720	960
出料口调节范围 Adjusting Range Discharging Opening	mm	65-160	80-140	95-180	85-220	120-260
处理量 Capacity(t/h)	t/h	90-180	110-320	220-450	130-360	260-580
给料机型号 Vibrating Feeder		GZD-960×3800	GZD-1100×4200	GZD-1300×4900	GZD-1300×4900	GZD-1300×4900
主皮带机型号 Main Belt Conveyor		B800×8.5m	B1000×9m	B1200×9.5m	B1200×9.5m	B1200×9.5m
侧出皮带机型号 (选配) Side-opening Belt Conveyor (Optional)		B450×3m	B500×3.5m	B650×4m	B650×4m	B650×4m
发电机组型号 (选配) Power of Generator Set (Optional)	Kw	160	200	220	250	300
除铁器型号 (选配) Iron-separator (Optional)		RCMD(C)-8	RCMD(C)-10	RCMD(C)-12	RCMD(C)-12	RCMD(C)-12



项目 Item	单位 Unit	MG938F1010	MG938F1210	MG1142F1214	MG1142F1315
运输长度 Transportation Length	mm	10800	11900	13100	13100
运输宽度 Transportation Width	mm	2480	2550	2800	2900
运输高度 Transportation Height	mm	3900	3900	4450	4450
最大长度 Maximum Length	mm	11200	12100	13300	13300
最大宽度 Maximum Width	mm	2900	2900	2950	2950
最大高度 Maximum Height	mm	4100	4100	5200	5200
重量 Weight	t	28	39	44	54
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装双轴 Dual-axial	并装三轴 Tri-axial	并装三轴 Tri-axial
破碎机型号 Crusher		PF-1010	PF-1210	PF-1214	PF-1315
最大进料 Max Feeding Size	mm	300	300	300	350
处理量 Capacity(t/h)	t/h	70-130	70-130	90-180	120-250
给料机型号 Vibrating Feeder		GZD-960×3800	GZD-960×3800	GZD-1100×4200	GZD-1100×4200
主皮带机型号 Main Belt Conveyor		B800×8m	B800×8.5m	B1000×9m	B1000×9m
侧出皮带机型号 (选配) Side-opening Belt Conveyor (Optional)		B450×3m	B450×3.2m	B500×3.5m	B500×3.5m
发电机组型号 (选配) Power of Generator Set (Optional)	kw	200	200	250	330
除铁器型号 (选配) Iron-separator (Optional)		RCMD(C)-8	RCMD(C)-8	RCMD(C)-10	RCMD(C)-10



项目 Item	单位 Unit	M3S1848F1010	M3S1848F1210	M3S1860F1214	M3S2160F1315
运输长度 Transportation Length	mm	14000	14200	16000	16000
运输宽度 Transportation Width	mm	3100	3100	3100	3200
运输高度 Transportation Height	mm	4400	4400	4400	4500
最大长度 Maximum Length	mm	14400	14600	16400	16400
最大宽度 Maximum Width	mm	3400	3400	3400	3500
最大高度 Maximum Height	mm	4700	5100	5100	5500
重量 Weight	t	34.5	35	41.5	47.5
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装双轴 Dual-axial	并装三轴 Tri-axial	并装三轴 Tri-axial
破碎机型号 Crusher		PF-1010	PF-1210	PF-1214	PF-1315
筛下皮带机 Belt Conveyor under Vibrating Screen		B800×6m	B800×6m	B800×7m	B1000×7m
振动筛型号 Vibrating Screen		3YZS1848	3YZS1848	3YZS1860	3YZS2160



项目 Item	单位 Unit	M3S1848CS75	M3S1860CS160	M3S1860HP220
运输长度 Transportation Length	mm	14000	16000	16000
运输宽度 Transportation Width	mm	3100	3100	3100
运输高度 Transportation Height	mm	4300	4500	4500
最大长度 Maximum Length	mm	14000	16400	16400
最大宽度 Maximum Width	mm	3400	3400	3400
最大高度 Maximum Height	mm	4700	4700	4700
重量 Weight	t	34.5	49.5	41
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装三轴 Tri-axial	并装三轴 Tri-axial
破碎机型号 Crusher		CS75	CS160	HP220
筛下皮带机 Belt Conveyor under Vibrating Screen		B800×6m	B800×7m	B800×7m
振动筛型号 Vibrating Screen		3YZS1848	3YZS1860	3YZS1860



项目 Item	单位 Unit	M3S1848V7611	M3S1848V8518	M3S1860V9526	M3S2160V1140
运输长度 Transportation Length	mm	9800	13500	15600	15600
运输宽度 Transportation Width	mm	2460	2830	2830	3100
运输高度 Transportation Height	mm	4200	4350	4350	4480
最大长度 Maximum Length	mm	10900	14650	16300	16300
最大宽度 Maximum Width	mm	3900	3900	3900	3900
最大高度 Maximum Height	mm	5830	5980	6400	6550
重量 Weight	t	26	31	36	49
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装双轴 Dual-axial	并装三轴 Tri-axial	并装三轴 Tri-axial
破碎机型号 Crusher		VSI7611	VSI8518	VSI9526	VSI1140
出料皮带机 Discharging Belt Conveyor		B800×2.2m	B800×2.2m	B800×2.5m	B1000×2.5m
筛下皮带机 Belt Conveyor under Vibrating Screen		B800×7m	B800×7m	B800×8m	B1000×8m
振动筛型号 Vibrating Screen		3YZS1848	3YZS1848	3YZS1860	3YZS2160



项目 Item	单位 Unit	M3S1848	M3S1860	M3S2160
运输长度 Transportation Length	mm	10100	11100	11100
运输宽度 Transportation Width	mm	2800	2820	3100
运输高度 Transportation Height	mm	4350	4350	4350
最大长度 Maximum Length	mm	11100	11800	11800
最大宽度 Maximum Width	mm	3600	3600	3970
最大高度 Maximum Height	mm	6000	6500	6500
重量 Weight	t	16	18	19
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装双轴 Dual-axial	并装双轴 Dual-axial
出料皮带机 Discharging Belt Conveyor		B800×7m	B800×8m	B1000×8m
振动筛型号 Vibrating Screen		3YZS1848	3YZS1860	3YZS2160



项目 Item	单位 Unit	ME46C24	ME57C24
运输长度 Transportation Length	mm	13700	14000
运输宽度 Transportation Width	mm	2800	2800
运输高度 Transportation Height	mm	4500	4600
最大长度 Maximum Length	mm	14500	14650
最大宽度 Maximum Width	mm	2800	2800
最大高度 Maximum Height	mm	5830	5980
重量 Weight	t	38	45
轮胎配置 Tire Configuration		并装双轴 Dual-axial	并装双轴 Dual-axial
喂料机型号 Vibrating Feeder		GZD960×3800	GZD960×3800
破碎机型号 Crusher		PE400×600	PE500×750
出料皮带机 Discharging Belt Conveyor		B650×6.5m	B650×6.5m
筛上皮带机 Belt Conveyor above Vibrating Screen		B650×10.5m	B650×10.5m
振动筛型号 Vibrating Screen		3YZS1237	3YZS1237



地址：上海市浦东新区金海路1000号

电话：021-66039988

传真：021-66030508

邮编：201206

网址：www.shunky.com www.shunky.cn

Email：Service@shunky.com



注：本手册内容如有变更恕不另行通知。

